

Tabele kombinacji jednostek

Jednostki zewnętrzne	Jednostki wewnętrzne ścienne											
	Energy SE				Mini Apple Pro					Apple Pie Pro		
	KA				TG					TG		
	25	35	50	70	20	25	35	50	70	25	35	50
2AMW42U4RGC	●	●			●	●	●			●	●	
2AMW52U4RXC	●	●			●	●	●			●	●	
3AMW62U4RJC	●	●	●		●	●	●	●		●	●	●
3AMW72U4RJC	●	●	●		●	●	●	●		●	●	●
4AMW81U4RJC	●	●	●		●	●	●	●		●	●	●
4AMW105U4RAA	●	●	●		●	●	●	●		●	●	●
5AMW125U4RTA	●	●	●	●	●	●	●	●	●	●	●	●

Jednostki zewnętrzne	Jednostki wewnętrzne LCAC Super Inverter											
	Kasetonowe				Kanałowe				Konsole			Przypodłogowo - podsufitowe
	ACT...CA4				ADT...L4 / AUD...L4				AKT...RK4			AVT...RA4
	25	35	50		25	35	50	70	25	35	50	50
2AMW42U4RGC	●	●			●	●			●	●		
2AMW52U4RXC	●	●			●	●			●	●		
3AMW62U4RJC	●	●	●		●	●	●		●	●	●	●
3AMW72U4RJC	●	●	●		●	●	●		●	●	●	●
4AMW81U4RJC	●	●	●		●	●	●		●	●	●	●
4AMW105U4RAA	●	●	●		●	●	●		●	●	●	●
5AMW125U4RTA	●	●	●	●	●	●	●	●	●	●	●	●

Jednostki zewnętrzne	Jednostki wewnętrzne LCAC Turbo Inverter											
	Kasetonowe				Kanałowe				Konsole			Przypodłogowo - podsufitowe
	ACT...C8				ADT...L8				AKT...RK8			AVT...RB8
	25	35	50	70	25	35	50		25	35	50	70
2AMW42U4RGC	●	●			●	●			●	●		
2AMW52U4RXC	●	●			●	●			●	●		
3AMW62U4RJC	●	●	●		●	●	●		●	●	●	
3AMW72U4RJC	●	●	●		●	●	●		●	●	●	
4AMW81U4RJC	●	●	●		●	●	●		●	●	●	
4AMW105U4RAA	●	●	●		●	●	●		●	●	●	
5AMW125U4RTA	●	●	●	●	●	●	●	●	●	●	●	●

Tabele konfiguracji jednostek

2AMW42U4RGC															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
25	2500					2500	1000	3200	700	330	1500	3,57	3,1	7,00	A++
35	3500					3500	1000	3800	1000	330	1500	3,50	4,4	7,10	A++
20+20	2050	2050				4100	1000	5500	950	330	2300	4,32	4,2	7,60	A++
20+25	1900	2200				4100	1000	5500	950	330	2300	4,32	4,2	7,80	A++
20+35	1800	2300				4100	1000	5500	920	330	2300	4,46	4,0	8,00	A++
25+25	2050	2050				4100	1000	5500	920	330	2300	4,46	4,0	8,00	A++
25+35	2000	2100				4100	1000	5500	920	330	2300	4,46	4,0	8,00	A++

2AMW52U4RXC															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+20	2000	2000				4000	1200	5000	1000	390	2000	4,00	4,4	7,40	A++
20+25	2000	2500				4500	1200	6000	1150	390	2300	3,91	5,1	7,50	A++
20+35	2000	3000				5000	1200	6600	1260	390	2500	3,97	5,5	7,50	A++
25+25	2500	2500				5000	1200	6600	1245	390	2500	4,02	5,5	7,60	A++
25+35	2300	2700				5000	1200	6600	1245	390	2500	4,02	5,5	7,65	A++
35+35	2500	2500				5000	1200	6600	1245	390	2500	4,02	5,5	7,65	A++

3AMW62U4RJC															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+25	2000	2500				4500	2000	8000	1300	500	3000	3,46	5,7	8,00	A++
20+35	2000	3500				5500	2000	8500	1400	500	3500	3,93	6,1	7,70	A++
20+50	2000	4300				6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
25+25	2500	2500				5000	2000	8000	1300	500	3000	3,85	5,7	7,70	A++
25+35	2500	3500				6000	2000	9000	1470	500	3900	4,08	6,5	8,00	A++
25+50	2300	4000				6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
35+35	3150	3150				6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
35+50	2500	3800				6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
20+20+20	2100	2100	2100			6300	2000	9000	1470	500	3900	4,29	6,5	7,80	A++
20+20+25	2000	2000	2300			6300	2000	9000	1470	500	3900	4,29	6,5	7,80	A++
20+20+35	1800	1800	2700			6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
20+20+50	1500	1500	3300			6300	2000	9000	1470	500	3900	4,29	6,5	8,10	A++
20+25+25	1700	2300	2300			6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
20+25+35	1500	2000	2800			6300	2000	9000	1470	500	3900	4,29	6,5	8,05	A++
20+25+50	1500	2000	2800			6300	2000	9000	1470	500	3900	4,29	6,5	8,10	A++
20+35+35	1300	2500	2500			6300	2000	9000	1470	500	3900	4,29	6,5	8,10	A++
20+35+50	1200	2300	2800			6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
25+25+25	2100	2100	2100			6300	2000	9000	1470	500	3900	4,29	6,5	8,00	A++
25+25+35	2000	2000	2300			6300	2000	9000	1470	500	3900	4,29	6,5	8,05	A++

2AMW42U4RGC															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
25	3000					3000	1000	3500	800	200	1500	3,75	3,5	5,31	A+++
35	4000					4000	1000	4500	1000	200	1500	4,00	4,4	5,31	A+++
20+20	2250	2250				4500	1000	6000	990	200	2300	4,55	4,3	5,31	A+++
20+25	2100	2400				4500	1000	6000	970	200	2300	4,64	4,3	5,31	A+++
20+35	2000	2500				4500	1000	6000	950	200	2300	4,74	4,2	5,31	A+++
25+25	2250	2250				4500	1000	6000	950	200	2300	4,74	4,2	5,31	A+++
25+35	2150	2350				4500	1000	6000	950	200	2300	4,74	4,2	5,31	A+++

2AMW52U4RXC															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+20	2300	2300				4600	1200	6500	1200	290	2000	3,83	5,3	5,31	A+++
20+25	2300	2700				5000	1200	6700	1300	290	2300	3,85	5,7	5,31	A+++
20+35	2000	3500				5500	1200	7000	1300	290	2500	4,23	5,7	5,31	A+++
25+25	2750	2750				5500	1200	7000	1300	290	2500	4,23	5,7	5,31	A+++
25+35	2500	3000				5500	1200	7000	1290	290	2500	4,26	5,7	5,31	A+++
35+35	2750	2750				5500	1200	7000	1280	290	2500	4,30	5,6	5,31	A+++

3AMW62U4RJC															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+25	2500	3500				6000	2000	8000	1500	500	3000	4,00	6,5	5,31	A+++
20+35	2600	3700				6300	2000	8500	1550	500	3500	4,06	6,7	5,31	A+++
20+50	2300	4700				7000	2000	9000	1570	500	3900	4,46	6,8	5,31	A+++
25+25	3000	3000				6000	2000	8500	1500	500	3500	4,00	6,5	5,31	A+++
25+35	3000	3700				6700	2000	9000	1520	500	3900	4,41	6,6	5,31	A+++
25+50	2420	4780				7200	2000	9000	1570	500	3900	4,59	6,9	5,31	A+++
35+35	3500	3500				7000	2000	9000	1570	500	3900	4,46	6,8	5,31	A+++
35+50	3000	4000				7000	2000	9000	1560	500	3900	4,49	6,8	5,31	A+++
20+20+20	2333	2333	2334			7000	2000	9000	1600	500	3900	4,38	7,0	5,31	A+++
20+20+25	2240	2240	2520			7000	2000	9000	1570	500	3900	4,46	6,9	5,31	A+++
20+20+35	2140	2140	2720			7000	2000	9000	1570	500	3900	4,46	6,9	5,31	A+++
20+20+50	1900	1900	3200			7000	2000	9000	1560	500	3900	4,49	6,9	5,31	A+++
20+25+25	2020	2490	2490			7000	2000	9000	1570	500	3900	4,46	6,9	5,31	A+++
20+25+35	2040	2180	2780			7000	2000	9000	1570	500	3900	4,46	6,9	5,31	A+++
20+25+50	1700	2000	3300			7000	2000	9000	1560	500	3900	4,49	6,9	5,31	A+++
20+35+35	1680	2660	2660			7000	2000	9000	1560	500	3900	4,49	6,9	5,31	A+++
20+35+50	1500	2300	3200			7000	2000	9000	1550	500	3900	4,52	6,8	5,31	A+++
25+25+25	2333	2333	2334			7000	2000	9000	1580	500	3900	4,43	6,9	5,31	A+++
25+25+35	2200	2200	2600			7000	2000	9000	1560	500	3900	4,49	6,9	5,31	A+++

Tabele konfiguracji jednostek

3AMW72U4RJC															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+25	2000	2500				4500	2000	6500	1300	440	2200	3,46	5,9	7,00	A++
20+35	2000	3500				5500	2000	8000	1450	460	2550	3,79	6,6	7,20	A++
20+50	2000	5000				7000	2000	10000	1750	500	3900	4,00	7,9	7,70	A++
25+25	2500	2500				5000	2000	7000	1400	460	2200	3,57	6,3	7,10	A++
25+35	2500	3500				6000	2000	8000	1570	500	3000	3,82	7,1	7,60	A+
25+50	2500	4500				7000	2000	10000	1750	500	3900	4,00	7,9	7,70	A++
35+35	3500	3500				7000	2000	10000	1750	500	3900	4,00	7,9	7,70	A++
35+50	2800	4200				7000	2000	10000	1730	500	3900	4,05	7,5	7,85	A++
50+50	3500	3500				7000	2000	10000	1710	500	3900	4,09	7,4	7,90	A++
20+20+20	2000	2000	2000			6000	2000	8000	1570	500	3000	3,82	7,1	7,60	A+
20+20+25	2000	2000	2500			6500	2000	9000	1660	500	3500	3,92	7,5	7,70	A++
20+20+35	2000	2000	3000			7000	2000	10000	1750	500	3900	4,00	7,9	7,80	A++
20+20+50	1800	1800	3400			7000	2000	10000	1730	500	3900	4,05	7,5	7,85	A++
20+25+25	2000	2500	2500			7000	2000	10000	1750	500	3900	4,00	7,9	7,80	A++
20+25+35	1700	2300	3000			7000	2000	10000	1750	500	3900	4,00	7,9	7,80	A++
20+25+50	1600	2000	3400			7000	2000	10000	1730	500	3900	4,05	8,0	7,85	A++
20+35+35	1600	2700	2700			7000	2000	10000	1730	500	3900	4,05	8,0	7,85	A++
20+35+50	1600	2200	3200			7000	2000	10000	1710	500	3900	4,09	8,0	7,90	A++
25+25+25	2333	2333	2334			7000	2000	10000	1750	500	3900	4,00	7,9	7,90	A++
25+25+35	2100	2100	2800			7000	2000	10000	1730	500	3900	4,05	8,0	7,95	A++
25+25+50	1800	1800	3400			7000	2000	10000	1710	500	3900	4,09	8,0	8,00	A++
25+35+35	2000	2500	2500			7000	2000	10000	1730	500	3900	4,05	8,0	7,95	A++
35+35+35	2333	2333	2334			7000	2000	10000	1710	500	3900	4,09	8,0	8,00	A++

4AMW81U4RJC															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+35	2100	3500				5600	2200	7000	1750	500	2700	3,20	7,8	7,00	A++
20+50	2100	4800				6900	2400	8000	1950	500	3300	3,54	8,7	7,00	A++
25+25	2600	2600				5200	2200	7000	1680	500	3000	3,10	7,5	6,90	A++
25+35	2600	3500				6100	2200	7200	1850	500	3100	3,30	8,3	6,95	A++
25+50	2600	4800				7400	2400	9000	2100	500	3500	3,52	9,4	7,05	A++
35+35	3500	3500				7000	2200	8000	2200	500	3100	3,18	9,9	7,00	A++
35+50	3200	4800				8000	2200	9500	2400	500	3500	3,33	10,7	7,10	A++
50+50	4000	4000				8000	2300	10500	2300	500	3800	3,48	10,3	7,25	A++
20+20+20	2100	2100	2100			6300	2400	8500	1900	540	3300	3,32	8,5	7,00	A++
20+20+25	2100	2100	2600			6800	2400	8700	1980	540	3500	3,43	8,9	7,00	A++
20+20+35	2100	2100	3200			7400	2400	9000	2130	540	3500	3,47	9,5	7,20	A++
20+20+50	1910	1910	4180			8000	2400	10500	2250	540	3800	3,56	10,1	7,30	A++
20+25+25	2100	2600	2600			7300	2400	9000	2200	540	3600	3,32	9,9	7,30	A++
20+25+35	2100	2600	3300			8000	2400	9500	2200	540	3700	3,64	9,9	7,25	A++
20+25+50	1810	2240	3950			8000	2400	10500	2150	540	3800	3,72	9,6	7,50	A++
20+35+35	2020	2990	2990			8000	2400	10000	2200	540	3700	3,64	9,9	7,25	A++
20+35+50	1800	2800	3400			8000	2400	10000	2150	540	3700	3,72	9,6	7,50	A++
25+25+25	2600	2600	2600			8000	2400	9500	2145	540	3700	3,73	9,6	7,50	A++
25+25+35	2540	2540	2920			8000	2400	10000	2145	540	3800	3,73	9,6	7,50	A++
25+25+50	2130	2130	3740			8000	2400	10500	2100	540	3950	3,81	9,4	7,50	A++
25+35+35	2370	2815	2815			8000	2400	10000	2145	540	3950	3,73	9,6	7,50	A++
25+35+50	2010	2480	3510			8000	2400	10500	2100	540	3800	3,81	9,4	7,50	A++
35+35+35	2667	2667	2667			8000	2400	10500	2145	540	3800	3,73	9,6	7,50	A++
20+20+20+20	2000	2000	2000	2000		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+20+25	1933	1933	1933	2200		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+20+35	1810	1810	1810	2570		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+20+50	1550	1550	1550	3350		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+25+25	1830	1830	2170	2170		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+25+35	1720	1720	2130	2430		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+20+35+35	1620	1620	2380	2380		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+25+25+25	1850	2050	2050	2050		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+25+25+35	1640	1930	1930	2500		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
20+25+35+35	1550	1920	2265	2265		8000	2600	10500	2130	580	3950	3,76	9,5	7,50	A++
25+25+25+25	2000	2000	2000	2000		8000	2600	10500	2130	580	3950	3,76	9,5	7,60	A++
25+25+25+35	1940	1940	1940	2180		8000	2600	10500	2130	580	3950	3,76	9,5	7,60	A++

3AMW72U4RJC															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+25	2500	3000				5500	2000	6500	1470	435	2250	3,74	6,4	5,31	A+++
20+35	2500	4000				6500	2000	8000	1700	435	2450	3,82	7,4	5,31	A+++
20+50	2600	5400				8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
25+25	3000	3000				6000	2000	7500	1590	435	2500	3,77	6,9	5,31	A+++
25+35	3300	3700				7000	2000	9000	1800	500	3500	3,89	7,8	5,31	A+++
25+50	2800	5200				8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
35+35	4000	4000				8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
35+50	3200	4800				8000	2000	10000	1980	500	3900	4,04	8,6	5,31	A+++
50+50	4000	4000				8000	2000	10000	1960	500	3900	4,08	8,5	5,31	A+++
20+20+20	2333	2333	2334			7000	2000	9000	1800	500	3500	3,89	7,8	5,31	A+++
20+20+25	2400	2400	2700			7500	2000	9500	1900	500	3700	3,95	8,3	5,31	A+++
20+20+35	2300	2300	3400			8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
20+20+50	2000	2000	4000			8000	2000	10000	1980	500	3900	4,04	8,6	5,31	A+++
20+25+25	2400	2800	2800			8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
20+25+35	2200	2600	3200			8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++
20+25+50	1800	2300	3900			8000	2000	10000	1980	500	3900	4,04	8,6	5,31	A+++
20+35+35	2100	2950	2950			8000	2000	10000	1980	500	3900	4,04	8,6	5,31	A+++
20+35+50	1700	2500	3800			8000	2000	10000	1960	500	3900	4,08	8,5	5,31	A+++
25+25+25	2666	2667	2667			8000	2000	10000	2000	500	3900	4,00	8,7	5,31	A+++</

Tabele konfiguracji jednostek

4AMW105U4RAA															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+50	2100	5000				7100	2400	8000	1950	500	3300	8,5	5,95	3,64	A++
25+50	2600	5000				7600	2400	9000	2100	500	3500	9,1	5,95	3,62	A++
35+35	3500	3500				7000	2200	8000	2050	500	3100	8,9	5,76	3,41	A++
35+50	3500	5000				8500	2200	9500	2310	500	3500	10,0	5,98	3,68	A++
50+50	5000	5000				10000	2200	10500	3150	500	4000	13,7	6,05	3,17	A++
20+20+25	2100	2100	2600			6800	2400	8700	1980	540	3500	8,6	6,11	3,43	A++
20+20+35	2100	2100	3500			7700	2400	9000	2130	540	3500	9,3	6,13	3,62	A++
20+20+50	2100	2100	5000			9200	2400	10500	2900	540	3800	12,6	6,19	3,17	A++
20+20+70	2000	2000	6000			10000	2400	11000	3120	540	4000	13,6	6,22	3,21	A++
20+25+25	2100	2600	2600			7300	2400	9000	2200	540	3600	9,6	6,11	3,32	A++
20+25+35	2100	2600	3500			8200	2400	9500	2400	540	3700	10,4	6,13	3,42	A++
20+25+50	2100	2600	5000			9700	2400	11000	3100	540	3800	13,5	6,19	3,13	A++
20+25+70	1900	2400	5700			10000	2400	11000	3120	540	4000	13,6	6,22	3,21	A++
20+35+35	2100	3500	3500			9100	2400	10000	2800	540	3700	12,2	6,15	3,25	A++
20+35+50	2050	3100	4850			10000	2400	11000	3120	540	4000	13,6	6,22	3,21	A++
20+50+50	1740	4130	4130			10000	2400	11500	3090	540	4000	13,4	6,35	3,24	A++
25+25+25	2600	2600	2600			7800	2400	9800	2300	540	3700	10,0	6,11	3,39	A++
25+25+35	2600	2600	3500			8700	2400	10000	2600	540	3800	11,3	6,13	3,35	A++
25+25+50	2550	2550	4900			10000	2400	11000	3100	540	4000	13,5	6,19	3,23	A++
25+25+70	2300	2300	5400			10000	2400	11000	3100	540	4000	13,5	6,19	3,23	A++
25+35+35	2600	3500	3500			9600	2400	10500	2850	540	3800	12,4	6,15	3,37	A++
25+35+50	2400	2960	4640			10000	2400	11500	3150	540	4000	13,7	6,22	3,17	A++
25+50+50	2060	3970	3970			10000	2400	11500	3100	540	4000	13,5	6,35	3,23	A++
35+35+35	3200	3200	3200			9600	2400	10500	2950	540	3800	12,8	6,21	3,25	A++
35+35+50	2800	2800	4400			10000	2400	11500	3100	540	4000	13,5	6,31	3,23	A++
35+50+50	2420	3790	3790			10000	2400	11500	3000	540	4000	13,0	6,39	3,33	A++
50+50+50	3300	3300	3300			9900	2600	11500	3100	540	4000	13,5	6,79	3,19	A++
20+20+20+20	2100	2100	2100	2100		8400	2600	10000	2450	580	3800	10,7	6,50	3,43	A++
20+20+20+25	2100	2100	2100	2600		8900	2600	10500	2600	580	4000	11,3	6,50	3,42	A++
20+20+20+35	2100	2100	2100	3200		9500	2600	11000	3070	580	4000	13,3	6,53	3,09	A++
20+20+20+50	1860	1860	1860	4420		10000	2600	11500	3090	580	4000	13,4	6,58	3,24	A++
20+20+25+25	2100	2100	2600	2600		9400	2600	11000	2900	580	4000	12,6	6,50	3,24	A++
20+20+25+35	2100	2100	2600	3200		10000	2600	11000	3080	580	4000	13,4	6,53	3,25	A++
20+20+25+50	1780	1780	2200	4240		10000	2600	11500	3100	580	4000	13,5	6,58	3,23	A++
20+20+35+35	1980	1980	3020	3020		10000	2600	11000	3080	580	4000	13,4	6,61	3,25	A++
20+20+35+50	1700	1700	2580	4020		10000	2600	11500	3080	580	4000	13,4	6,73	3,25	A++
20+20+50+50	1480	1480	3520	3520		10000	2600	11500	3050	580	4000	13,3	6,75	3,28	A++
20+25+25+25	2100	2600	2600	2600		9900	2600	11000	3100	580	4000	13,5	6,50	3,19	A++
20+25+25+35	2000	2480	2480	3040		10000	2600	11000	3100	580	4000	13,5	6,53	3,23	A++
20+25+25+50	1700	2110	2110	4080		10000	2600	11500	3080	580	4000	13,4	6,58	3,25	A++
20+25+35+35	1892	2342	2883	2883		10000	2600	11500	3090	580	4000	13,4	6,61	3,24	A++
20+25+35+50	1628	2016	2481	3876		10000	2600	11500	3080	580	4000	13,4	6,75	3,25	A++
20+25+50+50	1429	1769	3401	3401		10000	2600	11500	3050	580	4000	13,3	7,02	3,28	A++
20+35+35+35	1795	2735	2735	2735		10000	2600	11500	3100	580	4000	13,5	7,15	3,23	A++
20+35+35+50	1556	2370	2370	3704		10000	2600	11500	3080	580	4000	13,4	7,18	3,25	A++
25+25+25+25	2500	2500	2500	2500		10000	2600	11500	3100	580	4000	13,8	6,50	3,23	A++
25+25+25+35	2364	2364	2364	2909		10000	2600	11500	3100	580	4000	13,5	6,53	3,23	A++
25+25+25+50	2031	2031	2031	3906		10000	2600	11500	3080	580	4000	13,4	6,58	3,25	A++
25+25+35+35	2241	2241	2759	2759		10000	2600	11500	3100	580	4000	13,5	6,61	3,23	A++
25+25+35+50	1940	1940	2388	3731		10000	2600	11500	3080	580	4000	13,4	6,73	3,25	A++
25+25+50+50	1711	1711	3289	3289		10000	2600	11500	3050	580	4000	13,3	7,02	3,28	A++
25+35+35+35	2131	2623	2623	2623		10000	2600	11500	3100	580	4000	13,5	7,15	3,23	A++
25+35+35+50	1857	2286	2286	3571		10000	2600	11500	3080	580	4000	13,4	7,18	3,25	A++
35+35+35+35	2500	2500	2500	2500		10000	2600	11500	3100	580	4000	13,5	7,20	3,23	A++
35+35+35+50	2192	2192	2192	3425		10000	2600	11500	3080	580	4000	13,4	7,20	3,25	A++

4AMW105U4RAA															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+50	2600	5800				8400	2000	8500	2300	400	2833	10,0	3,83	3,65	A+
25+50	3000	5800				8800	2000	9500	2350	400	3167	10,2	3,83	3,74	A+
35+35	3700	3700				7400	1800	8700	2250	400	2900	9,8	3,81	3,29	A+
35+50	3700	5800				9500	1800	9700	2470	400	3233	10,7	3,84	3,85	A+
50+50	5500	5500				11000	1800	11000	2790	400	3667	12,1	3,89	3,94	A+
20+20+25	2600	2600	3000			8200	2200	9200	2110	420	3067	9,2	3,85	3,89	A+
20+20+35	2600	2600	3700			8900	2200	9500	2530	420	3167	11,0	3,86	3,52	A+
20+20+50	2600	2600	5800			11000	2200	10500	2750	420	3500	12,0	3,88	4,00	A+
20+20+70*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
20+25+25	2600	3000	3000			8600	2200	9500	2670	420	3167	11,6	3,85	3,22	A+
20+25+35	2600	3000	3700			9300	2200	10000	2690	420	3333	11,7	3,86	3,46	A+
20+25+50	2509	2895	5596			11000	2200	10500	2710	420	3500	11,8	3,88	4,06	A+
20+25+70*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
20+35+35	2600	3700	3700			10000	2200	10000	2730	420	3333	11,9	3,84	3,66	A+
20+35+50	2364	3364	5273			11000	2200	10500	2750	420	3500	12,0	3,87	4,00	A+
20+50+50	2014	4493	4493			11000	2200	11000	2770	420	3667	12,0	3,91	3,97	A+
25+25+25	3000	3000	3000			9000	2200	10000	2790	420	3333	12,1	3,85	3,23	A+
25+25+35	3000	3000	3700			9700	2200	10000	2810	420	3333	12,2	3,86	3,45	A+
25+25+50	2797	2797	5407			11000	2200	10500	2830	420	3500	12,3	3,88	3,89	A+
25+25+70*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
25+35+35	3000	3700	3700			10400	2200	10000	2750	420	3333	12,0	3,84	3,78	A+
25+35+50	2640	3256	5104			11000	2200	10500	2770	420	3500	12,0	3,87	3,97	A+
25+50+50	2260	4370	4370			11000	2200	12000	2790	420	4000	12,1	3,91	3,94	A+
35+35+35	3667	3667	3667			11000	2200	10500	2790	420	3500	12,1	3,93	3,94	A+
35+35+50	3083	3083	4833			11000	2200	10000	2810	420	3333	12,2	3,97	3,91	A+
35+50+50	2660	4170	4170			11000	2200	12000	2820	420	4000	12,3	4,01	3,90	A+
50+50+50	3500	3500	3500			10500	2200	12000	2850	420	4000	12,4	4,05	3,68	A+
20+20+20+20	2600	2600	2600	2600		10400	2200	12000	2550	460	2878	11,1	4,01	4,08	A+
20+20+20+25	2600	2600	2600	3000		10800	2200	12000	2660	460	2878	11,6	4,01	4,06	A+
20+20+20+35	2487	2487	2487	3539		11000	2200	12000	2660	460	2878	11,6	4,03	4,14	A+
20+20+20+50	2103	2103	2103	4691		11000	2200	12000	2680	460	2967	11,7	4,07	4,10	A+
20+20+25+25	2554	2554	2946	2946		11000	2200	12000	2660	460	2878	11,6	4,01	4,14	A+
20+20+25+35	2403	2403	2773	3420		11000	2200	12000	2660	460	2967	11,6	4,03	4,14	A+
20+20+25+50	2043	2043	2357	4557		11000	2200	12000	2810	460	2967	12,2	4,07	3,91	A+
20+20+35+35	2270	2270	3230	3230		11000	2200	12000	2750	460	2849	12,0	4,04	4,00	A+
20+20+35+50	1946	1946	2769	4340		11000	2200	12000	2810	460	2967	12,2	4,09	3,91	A+
20+20+50+50	1702	1702	3798	3798		11000	2200	12000	2820	460	2967	12,3	4,11	3,90	A+
20+25+25+25	2466	2845	2845	2845		11000	2200	12000	2750	460	2849	12,0	4,01	4,00	A+
20+25+25+35	2325	2683	2683	3309		11000	2200	12000	2750	460	2849	12,0	4,03	4,00	A+
20+25+25+50	1986	2292	2292	4431		11000	2200	12000	2810	460	2967	12,2	4,07	3,91	A+
20+25+35+35	2200	2538	3131	3131		11000	2200	12000	2800	460	2967	12,2	4,04	3,93	A+
20+25+35+50	1894	2185	2695	4225		11000	2200	12000	2810	460	2967	12,2	4,09	3,91	A+
20+25+50+50	1663	1919	3709	3709		11000	2200	12000	2820	460	2967	12,3	4,11	3,90	A+
20+35+35+35	2088	2971	2971	2971		11000	2200	12000	2800	460	2967	12,2	4,06	3,93	A+
20+35+35+50	1810	2576	2576	4038		11000	2200	12000	2810	460	2967	12,2	4,05	3,91	A+
25+25+25+25	2750	2750	2750	2750		11000	2200	12000	2800	460	4000	12,4	4,01	3,93	A+
25+25+25+35	2598	2598	2598	3205		11000	2200	12000	2800	460	4000	12,5	4,03	3,93	A+
25+25+25+50	2230	2230	2230	4311		11000	2200	12000	2810	460	4000	12,5	4,05	3,91	A+
25+25+35+35	2463	2463	3037	3037		11000	2200	12000	2800	460	4000	12,5	4,07	3,93	A+
25+25+35+50	2129	2129	2626	4116		11000	2200	12000	2810	460	4000	12,5	4,09	3,91	A+
25+25+50+50	1875	1875	3625	3625		11000	2200	12000	2820	460	4000	12,5	4,11	3,90	A+
25+35+35+50	2340	2887	2887	2887		11000	2200	12000	2800	460	4000	12,5	4,13	3,93	A+
25+35+35+50	2037	2512	2512	3938		11000	2200	12000	2810	460	4000	12,5	4,15	3,91	A+
35+35+35+35	2750	2750	2750	2750		11000	2200	12000	2800	460	4000	12,5	4,12	3,93	A+
35+35+35+50	2408	2408	2408	3775		11000	2200	12000	2810	460	4000	12,5	4,13	3,91	A+

Tabele konfiguracji jednostek

5AMW125U4RTA															
Kombinacja jednostek wewnętrznych	Wydajność chłodnicza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			EER	(A)	SEER	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+20+50	2000	2000	5000			9000	3000	9450	2400	552	3648	10,4	5,80	3,75	A++
20+20+70	2000	2000	7000			11000	3000	11550	2400	552	3648	10,4	5,80	4,58	A++
20+25+50	2000	2600	5000			9600	3000	10080	2400	552	3648	10,4	5,80	4,00	A++
20+25+70	2000	2600	7000			11600	3000	12180	2400	552	3648	10,4	5,80	4,83	A++
20+35+50	2000	3500	5000			10500	3000	11025	2400	552	3648	10,4	5,80	4,38	A++
20+35+70	2000	3500	7000			12500	3000	13125	2400	552	3648	10,4	5,80	5,21	A++
20+50+50	2000	5000	5000			12000	3000	12600	2400	552	3648	10,4	5,80	5,00	A++
20+50+70	1800	4500	6200			12500	3000	13125	2400	552	3648	10,4	5,80	5,21	A++
25+25+50	2600	2600	5200			10400	3400	10920	2400	552	3648	10,4	5,80	4,33	A++
25+25+70	2600	2600	7000			12200	3400	12810	2500	575	3800	10,8	5,80	4,88	A++
25+35+35	2600	3500	3500			9600	3400	10080	2500	575	3800	10,8	5,80	3,84	A++
25+35+50	2600	3500	5200			11300	3400	11865	2500	575	3800	10,8	5,80	4,52	A++
25+35+70	2500	3500	6500			12500	3400	13125	2500	575	3800	10,8	5,80	5,00	A++
25+50+50	2600	4900	5000			12500	3400	13125	2500	575	3800	10,8	6,05	5,00	A++
25+50+70	2300	4200	6000			12500	3400	13125	2500	575	3800	10,8	6,52	5,00	A++
35+35+35	3500	3500	3500			10500	3400	11025	2500	575	3800	10,8	6,52	4,20	A++
35+35+50	3500	3500	5000			12000	3400	12600	2500	575	3800	10,8	6,50	4,80	A++
35+35+70	3000	3000	6500			12500	3400	13125	2500	575	3800	10,8	6,50	5,00	A++
35+50+50	3100	4700	4700			12500	3400	13125	2500	575	3800	10,8	6,48	5,00	A++
35+50+70	3000	4000	5500			12500	3400	13125	2500	575	3800	10,8	6,49	5,00	A++
50+50+50	4200	4200	4100			12500	3400	13125	2500	575	3800	10,8	6,48	5,00	A++
20+20+20+20	2000	2000	2000	2000		8000	3000	8400	2000	460	3040	8,6	6,48	4,00	A++
20+20+20+25	2000	2000	2000	2500		8500	3000	8925	2100	483	3192	9,1	6,48	4,05	A++
20+20+20+35	2000	2000	2000	3500		9500	3000	9975	2200	506	3344	9,5	6,48	4,32	A++
20+20+20+50	2000	2000	2000	5000		11000	3000	11550	2300	529	3496	9,9	6,48	4,78	A++
20+20+20+70	2000	2000	2000	6500		12500	3000	13125	2400	552	3648	10,4	6,48	5,21	A++
20+20+25+25	2000	2000	2500	2500		9000	3000	9450	2200	506	3344	9,5	6,48	4,09	A++
20+20+25+35	2000	2000	2500	3500		10000	3000	10500	2300	529	3496	9,9	6,48	4,35	A++
20+20+25+50	2000	2000	3500	5000		12500	3000	13125	2400	552	3648	10,4	6,48	5,21	A++
20+20+25+70	2000	2000	2500	6000		12500	3000	13125	2400	552	3648	10,4	6,48	5,21	A++
20+20+35+35	2000	2000	3500	3500		11000	3000	11550	2300	529	3496	9,9	6,48	4,78	A++
20+20+35+50	2000	2000	2500	5000		11500	3000	12075	2400	552	3648	10,4	6,48	4,79	A++
20+20+35+70	2000	2000	3000	5500		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+20+50+50	2000	2000	4250	4250		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+20+50+70	1500	1500	3850	5650		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+25+25+25	2000	2500	2500	2500		9500	3000	9975	2700	621	4104	11,7	6,48	3,52	A++
20+25+25+35	2000	2500	2500	3500		10500	3000	11025	2700	621	4104	11,7	6,48	3,89	A++
20+25+25+50	2000	2500	2500	5000		12000	3000	12600	2700	621	4104	11,7	6,48	4,44	A++
20+25+25+70	1900	2300	2300	6000		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+35+35+35	2000	3500	3500	3500		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+35+35+50	2000	3000	3000	4500		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
20+35+35+70	1500	2500	2500	6000		12500	3000	13125	2700	621	4104	11,7	6,48	4,63	A++
25+25+25+25	2600	2600	2600	2600		10400	3400	10920	2700	621	4104	11,7	6,60	3,85	A++
25+25+25+35	2600	2600	2600	3500		11300	3400	11865	2750	632,5	4180	11,9	6,70	4,11	A++
25+25+25+50	2500	2500	2500	5000		12500	3400	13125	2800	644	4256	12,1	6,75	4,46	A++
25+25+25+70	2000	2000	2000	6500		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+25+35+35	2500	2500	3500	3500		12000	3400	12600	2800	644	4256	12,1	6,73	4,29	A++
25+25+35+50	2500	2500	3200	4300		12500	3400	13125	2800	644	4256	12,1	6,75	4,46	A++
25+25+35+70	2000	2000	3000	5500		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+25+50+50	2000	2000	4250	4250		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+25+50+70	1900	1900	3700	5000		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+35+35+35	2300	3400	3400	3400		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+35+35+50	2200	3000	3000	4300		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
25+35+35+70	1900	2400	2400	5800		12500	3400	13125	2800	644	4256	12,1	6,76	4,46	A++
35+35+35+35	3100	3100	3100	3200		12500	3400	13125	2800	644	4256	12,1	6,75	4,46	A++
35+35+35+50	2700	2700	2700	4400		12500	3400	13125	2800	644	4256	12,1	6,80	4,46	A++
20+20+20+20+20	2500	2500	2500	2500	2500	12500	3500	12300	3610	830,3	5487,2	15,6	6,50	3,46	A++
20+20+20+20+35	2300	2300	2300	2300	3300	12500	3500	13125	3700	851	5624	16,0	6,51	3,38	A++
20+20+20+20+50	2000	2000	2000	2000	4500	12500	3500	13125	3800	874	5776	16,4	6,53	3,29	A++
20+25+25+35+35	2000	2000	2000	3250	3250	12500	3500	13125	3750	862,5	5700	16,2	6,52	3,33	A++
20+25+35+35+35	2050	2050	2800	2800	2800	12500	3500	13125	3800	874	5776	16,4	6,53	3,29	A++

5AMW125U4RTA															
Kombinacja jednostek wewnętrznych	Wydajność grzewcza														
	A	B	C	D	E	Wydajność całkowita (W)			Pobór mocy (W)			COP	(A)	SCOP	Klasa
	W	W	W	W	W	NOM	MIN	MAX	NOM	MIN	MAX	W/W			
20+20+50	2500	2500	5500			10500	3000	10920	2400	413	3168	10,6	3,75	4,38	A+
20+20+70	2500	2500	7500			12500	3000	13000	2400	413	3168	10,6	3,75	5,21	A+
20+25+50	2500	3000	5500			11000	3000	11440	2400	413	3168	10,6	3,75	4,58	A+
20+25+70	2500	3000	7500			13000	3000	13520	2400	413	3168	10,6	3,75	5,42	A+
20+35+50	2500	4000	5500			12000	3000	12480	2400	413	3168	10,6	3,75	5,00	A+
20+35+70	2500	4000	7000			13500	3000	14040	2400	413	3168	10,6	3,75	5,63	A+
20+50+50	2500	5500	5500			13500	3000	14040	2400	413	3168	10,6	3,75	5,63	A+
20+50+70	2500	4500	6500			13500	3000	14040	2400	413	3168	10,6	3,75	5,63	A+
25+25+50	3000	3000	5500			11500	3000	11960	2400	413	3168	10,6	3,75	4,79	A+
25+25+70	3000	3000	7500			13500	3000	14040	2500	430	3300	11,0	3,75	5,40	A+
25+35+35	3000	4000	4000			11000	3000	11440	2500	430	3300	11,0	3,75	4,40	A+
25+35+50	3000	4000	5500			12500	3000	13000	2500	430	3300	11,0	3,75	5,00	A+
25+35+70	3000	3500	7000			13500	3000	14040	2500	430	3300	11,0	3,76	5,40	A+
25+50+50	3000	5250	5250			13500	3000	14040	2500	430	3300	11,0	3,78	5,40	A+
25+50+70	2500	4500	6500			13500	3000	14040	2500	430	3300	11,0	3,81	5,40	A+
35+35+35	4000	4000	4000			12000	3000	12480	2500	430	3300	11,0	3,81	4,80	A